



FastReport .NET

Programmers Manual

Version 2022.2

© 2008-2022 Fast Reports Inc.

General information

[Installing into VS Toolbox](#)

[Troubleshooting](#)

[Deployment](#)


[Compiling the source code](#)

[Credits](#)

Installing into VS Toolbox

To add FastReport .NET components to the Visual Studio toolbox, you need to do the following steps:

- delete the "FastReport .NET" tab from the Toolbox, if it is there;
- create a new tab (to do this, right-click the Toolbox and select "Add Tab" item), or select an existing tab you would like to add FastReport components to;
- right-click on a tab and select "Choose Items...":



- in the dialog, press the "Browse..." button and choose FastReport.dll, FastReport.Web.dll files (they are located in the "C:\Program Files\FastReports\FastReport.Net" folder);
- close the dialog with OK button.

After this, you will see FastReport .NET components in a chosen tab:



- Report;
- PreviewControl;
- DesignerControl;
- EnvironmentSettings;
- WebReport (this component will be visible in ASP.NET project only).

Troubleshooting

If you face a problem when working with report designer (for example, some toolbars or tool windows are damaged), you should delete the configuration file. This file is created when you start FastReport .NET. It is located in the following folder:

Windows XP:

```
C:\Documents and Settings\user_name\Local Settings\Application Data\FastReport\FastReport.config
```

Windows Vista:

```
C:\Users\user_name\AppData\Local\FastReport\FastReport.config
```

The following information is stored in the config:

- sizes and locations of dialog windows;
- toolbar settings;
- recent used data connections;
- email settings (if you use the "Send Email" feature in the preview).

Deployment

You may redistribute the following files along with your application:

- FastReport.dll - the main FastReport .NET library;
- FastReport.Web.dll - the library that contains ASP.Net WebReport component;
- FastReport.Bars.dll - the toolbars and docking windows library;
- FastReport.Editor.dll - the code editor with syntax highlight. This library is not needed if you don't provide an end-user designer;
- FastReport.Compat.dll - the library for cross-platform compatibility;
- FastReport.DataVisualization.dll - the library for drawing charts;
- FastReport.xml - comments for classes, properties and methods used in FastReport. This file is used by the script editor, and also by the hint panels in the "Data" and "Properties" windows. It's not obligatory to distribute this file.

If your reports are stored in files, you have to deploy them as well.

Compiling the source code

Source code is shipped with FastReport .NET Professional edition. It includes source code of FastReport.dll, FastReport.Web.dll libraries. You may include it in your application's solution file. Let us demonstrate how to do this:

- open your project in the Visual Studio;
- open the Solution Explorer and right-click on the "Solution" item;
- choose the "Add/Existing Project..." item;
- add the "FastReport.csproj" file (it is located in the "C:\Program Files\FastReports\FastReport.Net\Source\FastReport" folder);
- add the "FastReport.Web.csproj" file (it is located in the "C:\Program Files\FastReports\FastReport.Net\Source\FastReport.Web" folder).

Turn off assembly signing for FastReport and FastReport.Web projects. To do this:

- right-click the "FastReport" project in the Solution Explorer;
- choose the "Properties" item;
- switch to the "Signing" tab and uncheck the "Sign the assembly" checkbox;
- do the same steps for FastReport.Web project.

Update the references to other FastReport .NET assemblies. To do this:

- expand the "FastReport\References" item in the Solution Explorer;
- remove the "FastReport.Bars", "FastReport.Editor" references;
- right-click the "References" item and choose the "Add Reference..." item;
- add references to the "FastReport.Bars.dll" and "FastReport.Editor.dll" files. These files are located in the "C:\Program Files\FastReports\FastReport.Net" folder.

Credits

Toolbars and docking - DevComponents (<http://www.devcomponents.com>)

Code editor with syntax highlight - Quantum Whale (<http://www.qwhale.net>)

Silk icons set (<http://www.famfamfam.com/lab/icons/silk>)

Working with Windows.Forms

[Using the Report component in Visual Studio](#)

[Working with report in a code](#)

[Storing and loading a report](#)

[Registering data](#)

[Passing a value to a report parameter](#)

[Running a report](#)

[Designing a report](#)

[Exporting a report](#)

[Configuring the FastReport .NET environment](#)

[Replacing the "Open" and "Save" dialogs](#)

[Replacing the standard progress window](#)

[Passing own connection string](#)

[Passing custom SQL](#)

[Reference to a report object](#)

[Creating a report by using code](#)

[Using own preview window](#)

[Filtering tables in the Data Wizard](#)

Using the Report component in Visual Studio

Let us consider the typical use of the Report component in Visual Studio. We will use the data from a typed dataset.


- create a new Windows Forms application;
- add a dataset into it ("Data|Add New Data Source..." menu item);
- switch to the Form designer;
- add the "DataSet" component on a form and connect it to the typed dataset that you have created.

To create a report, perform the following steps:


- put the "Report" component on a form:



- right-click it (or click on a smart tag button) and select the "Design Report..." item:



- choose the data source to use in a report:



- create your report. Read more about this in the User's Manual;
- close the report designer;
- add a "Button" control on your form;
- double-click it and write the following code in the button_Click event handler:

```
report1.Show();
```

- save the project and run it. When you click on a button you will see the prepared report.

Working with report in a code

To work with Report component in a code, you need to do the following:

- create a report instance;
- load a report file into it;
- register the application-defined data in a report;
- pass the values into the report parameters, if needed;
- run the report.

The following example demonstrates how to do this:

```
using (Report report = new Report())
{
    report.Load("report1.frx");
    report.RegisterData(dataSet1, "NorthWind");
    report.Show();
}
```

We will consider these steps in details in the following sections of this manual.

Storing and loading a report

You may store a report in the following ways:

Method	Description	
in the application's resources	The typical scenario of using the Report, which we looked at before, uses this method. The StoreInResources property of the Report object is responsible for this. This property is set to true by default. This method has the following pros and cons: + a report is embedded into your application, you don't need to deploy extra files; - if you need to change a report, you have to recompile your application. Loading a report is performed automatically. To do this, FastReport .NET adds a code into the InitializeComponent method of your form.	
in the .FRX file	This method is useful if you want to give your users the ability to change a report. In this case, set the report's StoreInResources property to false. To load the report from a file, use the Load method of the Report object: <code>report1.Load("filename.frx");</code>	
in the database	You may store a report in the database, either as a string or in a blob-stream. To load the report from a string, use the LoadFromString method of the Report object. To load the report from a stream, use the overloaded version of the Load method: <code>report1.Load(stream);</code> To support the load/save operations in the report designer, you need to replace the "Open File" and "Save File" dialogs in the designer. Read here how to do this.	
as a C#/VB.NET class	To work with a report as a class, design your report and save in to the .cs/.vb file. To do this, select "file type" in the "Save" dialog. The file type maybe either .cs or .vb - it depends on the script language in the report (it may be changed in the "Report	Options..." menu). Include that file into your project. This method has the following pros and cons: + you can work with a report as a class; + you may debug a report; + this is the only way to use a report in ASP.NET project running on medium trust environment; - you cannot edit such a report. To do this, you need the original .FRX file; - if you need to change a report, you have to recompile your application. To work with a report, create an instance of the report's class: <pre>SimpleListReport report = new SimpleListReport(); report.Show();</pre>

Registering data

If your report uses data from an application (for example, the typed dataset or a business-object), you have to register such data in a report. This can be done using the RegisterData method of the Report object.

When you use the Report as described in the ["Using the Report component in Visual Studio"](#) section, you don't need to register the data. FastReport .NET does it automatically (it adds the RegisterData call in the InitializeComponent method of your form).

The RegisterData method must be called after you have loaded the report:

```
report1 = new Report();
report1.Load("report.frx");
report1.RegisterData(dataSet1, "NorthWind");
```

The RegisterData method is overloaded and allows to register the following data:

Method	Description
<code>void RegisterData(DataSet data)</code>	Registers the dataset. This method registers all tables, views and relations as well. Attention: if you register more than one dataset, use the RegisterData(DataSet data, string name) method instead.
<code>void RegisterData(DataSet data, string name)</code>	Registers the dataset. Specify any name in the name parameter (it must be persistent and unique if you register more than one dataset).
<code>void RegisterData(DataTable data, string name)</code>	Registers the data table.
<code>void RegisterData(DataView data, string name)</code>	Registers the data view.
<code>void RegisterDataAsp(IDataSource data, string name)</code>	Registers the ASP.NET data source such as AccessDataSource.
<code>void RegisterData(DataRelation data, string name)</code>	Registers the relation.
<code>void RegisterData(IEnumerable data, string name, BOConverterFlags flags, int maxNestingLevel)</code>	Registers the business object. Specify what items (properties, fields) should be used, in the flags parameter. Specify the maximum nesting level in the <code>maxNestingLevel</code> parameter (typically you need no more than 3 levels). Several nested objects may slow down the report.

Passing a value to a report parameter

The report may have parameters. Read more about this in the User's Manual. To pass a value to the parameter, use the `SetParameterValue` method of the Report object:

```
report1.Load("report.frx");  
report1.SetParameterValue("MyParam", 10);  
report1.Show();
```

This method is declared as follows:

```
public void SetParameterValue(string complexName, object value)
```

Specify the parameter's name in the `complexName` parameter. To access a nested parameter, use its full name, for example:

```
"ParentParameter.ChildParameter"
```

Running a report

To run a report, use one of the following methods of the Report object:

Method	Description
<code>void Show()</code>	<p>Runs a report and shows it in the preview window.</p> <p>This method is equal to:</p> <pre>if (Prepare()) ShowPrepared();</pre>
<code>bool Prepare()</code>	<p>Runs a report. If the report was prepared successfully, returns true. After this method, you need to call one of the following methods: ShowPrepared, PrintPrepared, SavePrepared, Export:</p> <pre>if (Prepare()) ShowPrepared();</pre>
<code>bool Prepare(bool append)</code>	<p>Runs a report. If the append parameter is set to true, the prepared report will be added to the existing one.</p> <p>So you can build several reports and display them in the preview as one report:</p> <pre>report1.Load("report1.frx"); report1.Prepare(); report1.Load("report2.frx"); report1.Prepare(true); report.ShowPrepared();</pre>
<code>void ShowPrepared()</code>	<p>Shows a prepared report in the preview window. The report must be either prepared using the Prepare method, or loaded from the .FPX file using the LoadPrepared method:</p> <pre>if (Prepare()) ShowPrepared();</pre>
<code>void ShowPrepared(bool modal)</code>	<p>Shows a prepared report in the preview window. The modal parameter determines whether the preview should be shown modally.</p>
<code>void ShowPrepared(bool modal, Form owner)</code>	<p>The same as the previous method. The owner parameter determines a window that owns the preview window.</p>
<code>void ShowPrepared(Form mdiParent)</code>	<p>The same as the previous method. The mdiParent parameter determines the main MDI window.</p>

Designing a report

You can use the report designer in your application. This is possible for all FastReport .NET editions except the Basic. To do this, use the Design method of Report object:

```
report1 = new Report();  
report1.Load("report1.frx");  
report1.Design();
```

The Design method is overloaded:

Method	Description
<code>bool Design()</code>	Shows the designer.
<code>bool Design(bool modal)</code>	Shows the designer. The modal parameter determines whether it is necessary to show the designer modally.
<code>bool Design(Form mdiParent)</code>	Shows the designer. The mdiParent parameter defines the main MDI window.

Exporting a report

The prepared report can be exported to one of the supported formats. At this moment, the following formats can be used:

- PDF
- HTML
- RTF
- Excel XML (Excel 2003+)
- Excel 2007
- CSV
- TXT
- OpenOffice Calc
- Pictures (Bmp, Png, Jpeg, Gif, Tiff, Metafile)

The export is performed by the export filter. To do this:

- prepare a report using the Prepare method;
- create an instance of export filter and set up its properties;
- call the Export method of the Report object.

The following example exports a prepared report in the HTML format:

```
// prepare a report
report1.Prepare();
// create an instance of HTML export filter
FastReport.Export.Html.HTMLExport export = new FastReport.Export.Html.HTMLExport();
// show the export options dialog and do the export
if (export.ShowDialog())
    report1.Export(export, "result.html");
```

In this example, export settings are made using the dialog window.

Configuring the FastReport .NET environment

Using the EnvironmentSettings component which is available in the Toolbox, you can control some FastReport .NET environment settings. To do this, put the component on your form and set up its properties using the Properties window.

The EnvironmentSettings.ReportSettings property contains some report-related settings:

Property	Description
<code>Language</code> <code>DefaultLanguage</code>	The default script language for new reports.
<code>bool</code> <code>ShowProgress</code>	Determines whether it is necessary to show the progress window.
<code>bool</code> <code>ShowPerformance</code>	Determines whether to show the information about the report performance (report generation time, memory consumed) in the lower right corner of the preview window.

The EnvironmentSettings.DesignerSettings property contains some designer-related settings:

Property	Description
<code>Icon</code> <code>Icon</code>	The icon for the designer window.
<code>Font</code> <code>DefaultFont</code>	The default font used in a report.

The EnvironmentSettings.PreviewSettings property contains some preview-related settings:

Property	Description
<code>PreviewButtons</code> <code>Buttons</code>	Set of buttons that will be visible in the preview's toolbar.
<code>int</code> <code>PagesInCache</code>	The number of prepared pages that can be stored in the memory cache during preview.
<code>bool</code> <code>ShowInTaskbar</code>	Determines whether the preview window is displayed in the Windows taskbar.
<code>bool</code> <code>TopMost</code>	Determines whether the preview window should be displayed as a topmost form.
<code>Icon</code> <code>Icon</code>	The icon for the preview window.
<code>string</code> <code>Text</code>	The text for the preview window. If no text is set, the default text "Preview" will be used.

The EnvironmentSettings.EmailSettings property contains email account settings. These settings are used in the "Send Email" feature in the preview window:

Property	Description
<code>string</code> <code>Address</code>	Sender address (e.g. your email address).

Property	Description
<code>string Name</code>	Sender name (e.g. your name).
<code>string MessageTemplate</code>	The message template that will be used to create a new message. For example, "Hello, Best regards, ...".
<code>string Host</code>	SMTP host address.
<code>int Port</code>	SMTP port (25 by default).
<code>string UserName, string Password</code>	User name and password. Leave these properties empty if your server does not require authentication.
<code>bool AllowUI</code>	Allows to change these settings in the "Send Email" dialog. Settings will be stored in the FastReport .NET configuration file.

UI style settings are available in the following properties of EnvironmentSettings component:

Property	Description
<code>UIStyle UIStyle</code>	The style of designer and preview form. 6 styles are available - VisualStudio2005, Office2003, Office2007Blue, Office2007Silver, Office2007Black, VistaGlass. The default style is Office2007Black.
<code>bool UseOffice2007Form</code>	This property affects the designer and preview form. It determines whether the Office2007-style form should be used if one of the following styles is selected: Office2007Blue, Office2007Silver, Office2007Black, VistaGlass. Default value is true.

Besides these properties, the EnvironmentSettings component has some events. Using such events, you may do the following:

- replace standard "Open file" and "Save file" dialogs in the designer;
- replace standard progress window;
- pass own connection string to a connection defined in the report.

These tasks will be described in the following sections of this manual.

Replacing the "Open" and "Save" dialogs

If you decided to store a report in the database, you may need to change the designer in such a way that it can open and save reports from/to a database. That is, you need to replace standard "Open" and "Save" dialogs with your own dialogs that work with database. To do this, use the EnvironmentSettings component (see the [Configuring the FastReport .NET environment](#)). This component has the following events:

Event `CustomOpenDialog`

Occurs when the report designer is about to show the "Open" dialog. In the event handler, you must display a dialog window to allow user to choose a report file. If dialog was executed successfully, you must return `e.Cancel = false` and set the `e.FileName` to the selected file name. The following example demonstrates how to use this event:

```
private void CustomOpenDialog_Handler(object sender, OpenSaveDialogEventArgs e)
{
    using (OpenFileDialog dialog = new OpenFileDialog())
    {
        dialog.Filter = "Report files (*.frx)|*.frx";
        // set e.Cancel to false if dialog
        // was successfully executed
        e.Cancel = dialog.ShowDialog() != DialogResult.OK;
        // set e.FileName to the selected file name
        e.FileName = dialog.FileName;
    }
}
```

Event `CustomSaveDialog`

Occurs when the report designer is about to show the "Save" dialog. In the event handler, you must display a dialog window to allow user to choose a report file. If dialog was executed successfully, you must return `e.Cancel = false` and set the `e.FileName` to the selected file name. The following example demonstrates how to use this event:

```
private void CustomSaveDialog_Handler(object sender, OpenSaveDialogEventArgs e)
{
    using (SaveFileDialog dialog = new SaveFileDialog())
    {
        dialog.Filter = "Report files (*.frx)|*.frx";
        // get default file name from e.FileName
        dialog.FileName = e.FileName;
        // set e.Cancel to false if dialog
        // was successfully executed
        e.Cancel = dialog.ShowDialog() != DialogResult.OK;
        // set e.FileName to the selected file name
        e.FileName = dialog.FileName;
    }
}
```

Event `CustomOpenReport`

Occurs when the report designer is about to load the report. In the event handler, you must load the report specified in the `e.Report` property from the location specified in the `e.FileName` property. The latter property contains the name that was returned by the `CustomOpenDialog` event handler. It may be the file name, the database key value, etc. The following example demonstrates how to use this event:

```
private void CustomOpenReport_Handler(object sender, OpenSaveReportEventArgs e)
{
    // load the report from the given e.FileName
    e.Report.Load(e.FileName);
}
```

Event `CustomSaveReport`

Occurs when the report designer is about to save the report. In the event handler, you must save the report specified in the `e.Report` property to the location specified in the `e.FileName` property. The latter property contains the name that was returned by the `CustomSaveDialog` event handler. It may be the file name, the database key value, etc. The following example demonstrates how to use this event:

```
private void CustomSaveReport_Handler(object sender, OpenSaveReportEventArgs e)
{
    // save the report to the given e.FileName
    e.Report.Save(e.FileName);
}
```

Replacing the standard progress window

The progress window is shown during the following actions:

- running a report
- printing
- exporting

You may turn off the progress by setting the `ReportSettings.ShowProgress` property of the `EnvironmentSettings` component to false. Besides that, you may replace the standard progress window with your own. To do this, use the following events of the `EnvironmentSettings` component (see the "[Configuring the FastReport .NET environment](#)" section):

Event	Description
<code>StartProgress</code>	Occurs once before the operation. In this event, you have to create your own progress window and show it.
<code>Progress</code>	Occurs each time when current report page is handled. In this event, you have to show the progress state in your window.
<code>FinishProgress</code>	Occurs once after the operation. In this event, you have to destroy the progress window.

The `Progress` event takes e parameter of `ProgressEventArgs` type. It has the following properties:

Property	Description
<code>string Message</code>	The message text.
<code>int Progress</code>	The index of current report page being handled.
<code>int Total</code>	The number of total pages in a report. This parameter may be 0 when preparing a report, because the number of total pages is unknown.

In most cases, you need to display the text from the `e.Message` property, in the `Progress` event handler. Other parameters may be useful if you want to display a progress bar.

Passing own connection string

If you use data sources that are defined inside a report, you may need to pass an application-defined connection string to a report. This can be done in three ways.

The first method: you pass a connection string directly to the Connection object in a report. Do the following:

```
report1.Load(...);
// do it after loading the report, before running it
// assume we have one connection in the report
report1.Dictionary.Connections[0].ConnectionString = my_connection_string;
report1.Show();
```

The second method: you pass a connection string using the report parameter. Do the following:

- run the report designer;
- in the "Data" window, create a new report parameter (with "MyParameter" name, for example). See the User's Manual for more details;
- in the "Data" window, select the "Connection" object that contains a data source;
- switch to the "Properties" window and set the ConnectionStringExpression property to the following:

```
[MyParameter]
```

- pass the connection string to the MyParameter parameter:

```
report1.SetParameterValue("MyParameter", my_connection_string);
```

The third method: use the DatabaseLogin event of the EnvironmentSettings component (see the ["Configuring the FastReport.NET environment"](#) section). This event occurs each time when FastReport opens the connection. Here is an example of this event handler:

```
private void environmentSettings1_DatabaseLogin(
    object sender, DatabaseLoginEventArgs e)
{
    e.ConnectionString = my_connection_string;
}
```

Keep in mind that the DatabaseLogin event is global, it works with all reports.

Passing custom SQL

The report may contain data sources that are added using the Data Wizard (via "Data|Add Data Source..." menu). Sometimes it is needed to pass custom SQL to that data source from your application. To do this, use the following code:

```
using FastReport.Data;
report1.Load(...);
// do it after loading the report, before running it
// find the table by its alias
TableDataSource table = report1.GetDataSource("MyTable") as TableDataSource;
table.SelectCommand = "new SQL text";
report1.Show();
```

Reference to a report object

When you work with a report as a class (see the ["Storing a report and loading it"](#) section), you may refer to the report objects directly. The following example demonstrates how to change the font of the "Text1" object contained in a report:

```
SimpleListReport report = new SimpleListReport();  
report.Text1.Font = new Font("Arial", 12);
```

In other cases, you have to use the FindObject method of the Report object, if you need to get a reference to an object:


```
TextObject text1 = report1.FindObject("Text1") as TextObject;  
text1.Font = new Font("Arial", 12);
```

To reference to a data source defined in a report, use the GetDataSource method of the Report object. This method takes a data source's alias as a parameter:

```
DataSourceBase ds = report1.GetDataSource("Products");
```

Creating a report by using code

Let us consider how to create a report in code. We will create the following report:



ReportTitle	PRODUCTS
Group Header: [[Products.ProductName].Substring(0, 1)]	[[Products.ProductName].Substring(0, 1)]
Data: Products	[Products.ProductName]
Group Footer	Count: [CountOfProducts]

```
Report report = new Report();

// register the "Products" table
report.RegisterData(dataSet1.Tables["Products"], "Products");

// enable it to use in a report
report.GetDataSource("Products").Enabled = true;

// create A4 page with all margins set to 1cm
ReportPage page1 = new ReportPage();
page1.Name = "Page1";
report.Pages.Add(page1);

// create ReportTitle band
page1.ReportTitle = new ReportTitleBand();
page1.ReportTitle.Name = "ReportTitle1";

// set its height to 1.5cm
page1.ReportTitle.Height = Units.Centimeters * 1.5f;

// create group header
GroupHeaderBand group1 = new GroupHeaderBand();
group1.Name = "GroupHeader1";
group1.Height = Units.Centimeters * 1;

// set group condition
group1.Condition = "[Products.ProductName].Substring(0, 1)";

// add group to the page.Bands collection
page1.Bands.Add(group1);

// create group footer
group1.GroupFooter = new GroupFooterBand();
group1.GroupFooter.Name = "GroupFooter1";
group1.GroupFooter.Height = Units.Centimeters * 1;

// create DataBand
DataBand data1 = new DataBand();
data1.Name = "Data1";
data1.Height = Units.Centimeters * 0.5f;

// set data source
data1.DataSource = report.GetDataSource("Products");

// connect databand to a group
group1.Data = data1;

// create "Text" objects
```

```

// report title
TextObject text1 = new TextObject();
text1.Name = "Text1";

// set bounds
text1.Bounds = new RectangleF(0, 0, Units.Centimeters * 19, Units.Centimeters * 1);

// set text
text1.Text = "PRODUCTS";

// set appearance
text1.HorzAlign = HorzAlign.Center;
text1.Font = new Font("Tahoma", 14, FontStyle.Bold);

// add it to ReportTitle
page1.ReportTitle.Objects.Add(text1);

// group
TextObject text2 = new TextObject();
text2.Name = "Text2";
text2.Bounds = new RectangleF(0, 0, Units.Centimeters * 2, Units.Centimeters * 1);
text2.Text = "[[Products.ProductName].Substring(0, 1)]";
text2.Font = new Font("Tahoma", 10, FontStyle.Bold);

// add it to GroupHeader
group1.Objects.Add(text2);

// data band
TextObject text3 = new TextObject();
text3.Name = "Text3";
text3.Bounds = new RectangleF(0, 0, Units.Centimeters * 10, Units.Centimeters * 0.5f);
text3.Text = "[[Products.ProductName]]";
text3.Font = new Font("Tahoma", 8);

// add it to DataBand
data1.Objects.Add(text3);

// group footer
TextObject text4 = new TextObject();
text4.Name = "Text4";
text4.Bounds = new RectangleF(0, 0, Units.Centimeters * 10, Units.Centimeters * 0.5f);
text4.Text = "Count: [CountOfProducts]";
text4.Font = new Font("Tahoma", 8, FontStyle.Bold);

// add it to GroupFooter
group1.GroupFooter.Objects.Add(text4);

// add a total
Total groupTotal = new Total();
groupTotal.Name = "CountOfProducts";
groupTotal.TotalType = TotalType.Count;
groupTotal.Evaluator = data1;
groupTotal.PrintOn = group1.Footer;

// add it to report totals
report.Dictionary.Totals.Add(groupTotal);

// run the report
report.Show();

```

The prepared report looks as follows:

PRODUCTS

A

Aniseed Syrup

Alice Mutton

Count: 2

B

Boston Crab Meat

Count: 1

Using own preview window

Using the EnvironmentSettings component (see the "[Configuring the FastReport .NET environment](#)" section), you may tune up the standard preview window. The related properties are contained inside the EnvironmentSettings.PreviewSettings property.

If you don't want to use the standard preview window for some reason, you may create your own. To do this, use the PreviewControl control that can be added on your form. To show a report in this control, connect it to the Report object by the following code:

```
report1.Preview = previewControl1;
```

To prepare a report and show it in the PreviewControl, use the Show method of the Report object:

```
report1.Show();  
your_form.ShowDialog();
```

or the following code:

```
if (report1.Prepare())  
{  
    report1.ShowPrepared();  
    your_form.ShowDialog();  
}
```

In these examples, the your_form is your form that contains the PreviewControl.

Using the methods of PreviewControl component, you can handle it from your code. You may even turn off the standard toolbar and/or statusbar, using the ToolbarVisible, StatusBarVisible properties. This is demonstrated in the Demos\C#\CustomPreview example project.

Filtering tables in the Data Wizard

The Data Wizard can be called from the "Data|Add Data Source..." menu. Here you can set up the connection and choose one or several data tables. By default, the wizard displays all tables available in the selected connection. If you want to filter unnecessary tables, use the `Config.DesignerSettings.FilterConnectionTables` event. The following example shows how to remove the "Table 1" table from the tables list:

```
using FastReport.Utils;
Config.DesignerSettings.FilterConnectionTables += FilterConnectionTables;
private void FilterConnectionTables(
    object sender, FilterConnectionTablesEventArgs e)
{
    if (e.TableName == "Table 1")
        e.Skip = true;
}
```

Working with ASP.NET

[Using the WebReport component](#)

[Setting up web handler](#)

[Storing and loading a report](#)

[Registering data](#)

[Passing a value to a report parameter](#)

[Working in the "Medium Trust" mode](#)

[Working in Web Farm and Web Garden architectures](#)

[Working with ASP.NET MVC](#)


[Example of export in MVC](#)

[FastReport .Net and jQuery](#)


Using the WebReport component

Let us consider the typical case of using the WebReport component.


- assuming that you have a web project with all necessary data sources (for example, AccessDataSource);
- put the WebReport component on your web form:



- in the "smart tag" menu, select the "Select Data Source..." item and choose one or several data sources which you want to use in a report:



- in the "smart tag" menu, select the "Design Report..." item to run the report designer:



- create a report. Read more about this in the User's Manual;
- close the designer;
- save the changes in your project and run it. You will see a window with a prepared report.

Setting up web handler

WebReport requires a specific handler to be set in the web.config file. When you create a report object in Visual Studio, necessary lines are automatically written to the configuration file. The WebReport component checks the availability of the specified configuration at run time of the application. If the required lines are not found in the web.config file an error is thrown, requesting the file to be changed.

The web.config file should contain the following lines when used with an IIS6 server:

```
<system.web>
...
<httpHandlers>
  <add path="FastReport.Export.axd" verb="*" type="FastReport.Web.Handlers.WebExport"/>
</httpHandlers>
...
</system.web>
```

and with an IIS7 server, these lines:

```
<system.webServer>
...
<handlers>
  <add name="FastReportHandler" path="FastReport.Export.axd" verb="*"
type="FastReport.Web.Handlers.WebExport"/>
</handlers>
...
</system.webServer>
```

The correct WebReport configuration lines in the web.config file must be used when transferring your project from one server to another.

Check for correct working of the WebReport handler by means of the URL:

http://yoursite/app_folder/FastReport.Export.axd

An information message gives the version of FastReport and the server time.

Storing and loading a report

You may store a report in the following ways:

In a web form:

Typical scenario that we have looked at before, uses this method. The report is stored in the `ReportResourceString` property of the `WebReport` component. This method has the following pros and cons:

- + it's a simplest way to work with `FastReport.Net`;
- the report template is stored in the `ViewState` of your web form. It will be transferred on a client side. It may slow down the work if the report has a big size;
- this method is not compatible with "Medium Trust" mode.

The report loading is performed automatically.

In the .FRX file:

This method assumes that the report is stored in a file in a special folder "App_Data". To do this:

- run the report designer;
- create a report and save it to the .FRX file;
- in the Solution Explorer, select the "App_Data" folder, right-click it and choose the "Add/Existing Item..." item. Select the report file that you just saved;
- select the `WebReport` component and clear its `ReportResourceString` property;
- select the "ReportFile" property, invoke its editor and choose the report from "App_Data" folder.

This method has the following pros and cons:

- + the report is not transferred to a client machine;
- this method is not compatible with "Medium Trust" mode.

The report loading is performed automatically.

A report can also be loaded from `WebReport.StartReport` event handler. Example code in `StartReport`:

```
(sender as WebReport).Report.Load(this.Server.MapPath("~/App_Data/report.frx"));
```

As a C#/VB.NET class:

In this method, you work with the report as a class. To do this:

- design your report and save in to the .cs/.vb file. To do this, select "file type" in the "Save" dialog. The file type maybe either .cs or .vb - it depends on the script language in the report (it may be changed in the "Report/Options..." menu);
- include that file into your project. It's better to save it in the "App_Code" folder;
- clear both `ReportResourceString` and `ReportFile` properties of the `WebReport` component.

This method has the following pros and cons:

- + you can work with the report as a regular class;
- + you can debug the report in the Visual Studio;
- + it's the only way to use a report in the "Medium Trust" mode;
- you cannot edit such a report. To do this, you need the original .FRX file.

To work with a report, create the `WebReport.StartReport` event handler. In this handler, you should do the following:

- create an instance of your report class;
- register the data;
- set the report to the `Report` property of the `WebReport` component.

Example of the `StartReport` event handler:

```
SimpleListReport report = new SimpleListReport();
report.RegisterDataAsp(your_data, "your_data_name");
WebReport1.Report = report;
```

The prepared report can be displayed from `WebReport.StartReport` event handler using the property `WebReport.ReportDone`. Example code in `StartReport` to load and display a prepared report:

```
(sender as WebReport).Report.LoadPrepared(this.Server.MapPath("~/App_Data/Prepared.fpx"));
(sender as WebReport).ReportDone = true;
```

Registering data

If you select the data source using the "smart tag" menu of the WebReport component, you don't need to register the data manually. In this case, FastReport.Net stores the names of data sources in the ReportDataSources property of the WebReport component.

In case you don't want to use such method of registering data, you need to do it manually. It can be done by using the StartReport event of the WebReport component. In this event handler, you can call the RegisterData and RegisterDataAsp methods of the report. The report can be accessed through the WebReport.Report property:

```
webReport1.Report.RegisterData(myDataSet);
```

Read more about registering data in [this section](#).

Passing a value to a report parameter

To pass a value to the report parameter, use the `SetParameterValue` method of the `Report` object. This method was described in details in the ["Working with Windows.Forms"](#) chapter.

To use this method in ASP.NET, you need to create the event handler for the `StartReport` event of the `WebReport` component. The report can be accessed through the `WebReport.Report` property:

```
webReport1.Report.SetParameterValue("MyParam", 10);
```

Working in the "Medium Trust" mode

This mode is used by many shared hosting providers. In this mode, the following actions are restricted:

- report compilation is impossible;
- impossible to use MS Access data source;
- impossible to use the RichObject;
- impossible to use some export filters that use WinAPI calls or temp files (PDF, Open Office);
- there may be other restrictions, depending on the provider.

To work with a report in this mode, you need to store a report as a C#/VB.NET class, as described in the ["Storing and loading a report"](#) section. In this case, the report compilation is not required.

Besides that, it is necessary to add System.Windows.Forms.DataVisualization.dll assembly into the GAC. This assembly is a part of Microsoft Chart Control and is used in FastReport to draw charts. Consult with your shared-hosting provider regarding adding this assembly into the GAC.

Working in Web Farm and Web Garden architectures

To use the FastReport report generator in a multi-server (Web Farm) or multi-processor (Web Garden) architecture there are additional requirements for creating special storage for data synchronization between WebReport objects.

Add the following lines to the configuration file web.config:

```
<appSettings>
<add key="FastReportStoragePath" value="\\FS\WebReport_Exchange"/>
<add key="FastReportStorageTimeout" value="10"/>
<add key="FastReportStorageCleanup" value="1"/>
</appSettings>
```

- FastReportStoragePath : path to the folder for temporary files when working in a multi-server architecture, each server must have access to this folder
- FastReportStorageTimeout : cache time for reports, in minutes
- FastReportStorageCleanup : time for checking the expired cache entries, in minutes

Check for correct configuration by means of the URL:

http://yoursite/app_folder/FastReport.Export.axd

You should see "Cluster mode: ON".

Working with ASP.NET MVC

You will not have any problems when using WebReport in ASPX (MVC 2) – it is only necessary to drag the control from the Toolbox to the page. WebReport will make all the required changes to web.config automatically. Let's look at a demo of WebReport in aspx, to be found in folder \Demos\C#\MvcDemo.

To use WebReport in Razor (MVC 3,4) you will need to add a line with the handler definitions to the web.config file in the root folder of your web-application.

Add this line in section <system.web> for use with IIS6:

```
<add path="FastReport.Export.axd" verb="*" type="FastReport.Web.Handlers.WebExport" />
```

and add this line in section <system.webServer> for use with IIS7:

```
<add name="FastReportHandler" path="FastReport.Export.axd" verb="*" type="FastReport.Web.Handlers.WebExport" />
```

Then modify the web.config file in the folder containing Views. Add these lines in section <system.web.webPages.razor> :

```
<add namespace="FastReport" />
```

```
<add namespace="FastReport.Web" />
```

Add these lines to file _Layout.cshtml in tag :

```
@WebReportGlobals.Scripts()
```

```
@WebReportGlobals.Styles()
```

Now you can draw the report on the View. Go to the controller and create a WebReport:

```
WebReport webReport = new WebReport(); // create object
```

```
webReport.Width = 600; // set width
webReport.Height = 800; // set height
webReport.Report.RegisterData(dataSet, "AppData"); // data binding
webReport.ReportFile = this.Server.MapPath("~/App_Data/report.frx"); // load the report from the file
ViewBag.WebReport = webReport; // send object to the View
```

Go to View and add the line:

```
@ViewBag.WebReport.GetHtml()
```

Similar code to create WebReport you can also write directly in View.

Let's look at the demo of WebReport in Razor in folder \Demos\C#\MvcRazor. There are various samples for loading into the report, including pre-prepared, and there is an example of using the event StartReport.

Don't forget to add the missing dll in the bin directory.

Example of export in MVC

When using FastReport.Net together with the ASP.Net MVC framework there is an easy method for creating a file in any supported format from a button press on the HTML form.

Add this code in the View:

```
@using (Html.BeginForm("GetFile", "Home"))
{
    <input id="pdf" type="submit" value="Export to PDF" />
}
```

- GetFile : name of the controller handler
- Home : name of the controller (eg: HomeController.cs)

Add the name space in the controller:

```
using FastReport.Export.Pdf;
```

Add method GetFile in the controller:

```
public FileResult GetFile()
{
    WebReport webReport = new WebReport();
    // bind data
    System.Data.DataSet dataSet = new System.Data.DataSet();
    dataSet.ReadXml(report_path + "nwind.xml");
    webReport.Report.RegisterData(dataSet, "NorthWind");

    // load report
    webReport.ReportFile = this.Server.MapPath("~/App_Data/report.frx");
    // prepare report
    webReport.Report.Prepare();
    // save file in stream
    Stream stream = new MemoryStream();
    webReport.Report.Export(new PDFExport(), stream);
    stream.Position = 0;
    // return stream in browser
    return File(stream, "application/zip", "report.pdf");
}
```

Example for Excel 2007:

```
using FastReport.Export.OoXML;
...
webReport.Report.Export(new Excel2007Export(), stream);
...
return File(stream, "application/xlsx", "report.xlsx");
```

FastReport .Net and jQuery

The WebReport object from FastReport.Net uses the jQuery library. You may already be using this library in your project.

To avoid duplication of jQuery boot scripts and styles in the client browser when working with markup Razor, you must use the following lines in `_Layout.cshtml`:

```
@WebReportGlobals.ScriptsWjQuery()  
@WebReportGlobals.StylesWjQuery()
```

replacing these lines, which include all jQuery files:

```
@WebReportGlobals.Scripts()  
@WebReportGlobals.Styles()
```

You must set the property `ExternalJquery = true` (defaults to false) when working with ASPX markup.

Working with WCF

[WCF service library FastReport.Service.dll](#)


[Simple example of WCF service](#)

[Creating Web Service using FastReport.Service.dll](#)

[Creating the WCF service hosted in windows service](#)

WCF service library FastReport.Service.dll

FastReport .NET contains the library FastReport.Service.dll (only in the .NET 4.0 package). This library is a WCF Service Library and is intended for use in custom applications that perform the functions of the service.



The library contains the following functions:

```
List<ReportItem> GetReportsList();
```

returns a list of available reports. Each item is returned as a ReportItem object. Reports are stored on a hard drive on a server that is running the service. Files are sorted in alphabetical order.

```
List<ReportItem> GetReportsListByPath(string path);
```

returns a list of available reports by path. Files are sorted in alphabetical order.

```
List<GearItem> GetGearList();
```

returns a list of available formats that can generate service reports as elements GearItem.

```
Stream GetReport(ReportItem report, GearItem gear);
```

returns a stream of the result of building a report. Parameters "report" and "gear" can be used from the lists previously obtained, or by creating new objects with the required properties. The returned stream does not support positioning.

Let's look at list elements.

ReportItem

```
public class ReportItem
{
    public string Path;
    public string Name;
    public string Description;
    public Dictionary<string, string> Parameters;
}
```

Path – path to the report file on the server, relative to the root folder for storing reports. The file extension of the report must be *.frx. This property is used to identify a specific report with further queries.

Name – name of the report, taken from the metadata of the report. If the metadata of the report contains an empty name then the property contains a filename without an extension. This property can be used to build an interactive list of available reports in your application (eg: in a ListBox).

Description – description of the report, taken from the metadata of the report.

Dictionary<string, string> Parameters – dictionary of report parameters, may be filling parameters, which will be subsequently transferred to the report. It supports only the string values that must be considered when designing a report template.

GearItem

```
public class GearItem
{
    public string Name;
    public Dictionary<string, string> Properties;
}
```

Name – name of the format : may contain one of the following strings:

Name	Description
PDF	Adobe Acrobat file
DOCX	Microsoft Word 2007 file
XLSX	Microsoft Excel 2007 file
PPTX	Microsoft PowerPoint 2007 file
RTF	Rich Text file – supported by many text editors
ODS	Open Office Spreadsheet file
ODT	Open Office Text file
MHT	Compressed HTML file together with the images, can be opened in Internet Explorer
CSV	Comma separated values file
DBF	dBase file
XML	Excel XML table – without images
TXT	Text file
FPX	FastReport.Net Prepared report file

Dictionary<string, string> Properties – dictionary of parameters of a report. A complete list of supported parameters with default values is available on requesting the server to list formats.

When creating a service you must add the following lines in your App.config or Web.config:

```

<appSettings>
<add key="FastReport.ReportsPath" value="C:\Program files\FastReports\FastReport.Net\Demos\WCF" />
<add key="FastReport.ConnectionStringName" value="FastReportDemo" />
<add key="FastReport.Gear" value="PDF,DOCX,XLSX,PPTX,RTF,ODS,ODT,MHT,CSV,DBF,XML,TXT,FPX" />
</appSettings>


```

FastReport.ReportsPath – specifies the path to the folder with the reports, a list of which will be transmitted to the client.

FastReport.ConnectionStringName – name of the connection string to the database, which is stored in the configuration section . Used to replace the internal connection string in the report template.

FastReport.Gear – list of available formats. You can select only those required and change the order of the names.

Schematic of using FastReport.Service:



And, if you already know exactly what to report and in which format to receive it (this reduces the number of queries made to the service):



Important points to note when you create report templates for use in the services:

- dialogs in the reports are not supported and will be ignored;
- each report must include an internal DataConnection, whose connection string for the report service is replaced by a string from the configuration.

Examples of use of FastReport.Service.dll can be found in the folders \Demos\C#\WCFWebService , \Demos\C#\WCFWindowsService , \Demos\C#\WCFWebClient , \Demos\C#\WCFClient.

An example configuration file service - FastReport.Service.dll.config.

Simple example of WCF service

This example does not require programming and is intended for testing the library and the configuration file. To complete the task, we will use the program WcfSvcHost.exe, that comes with Visual Studio:

1. Create a folder for our project anywhere on the disk, eg: as C:\WCF\FastReport
2. Copy these files to the folder : FastReport.Service.dll, FastReport.Service.dll.config, FastReport.dll and FastReport.Bars.dll
3. Create two sub-folders \Data and \Reports
4. Copy the database file to the \Data folder from the Demos folder \FastReport.Net\Demos\Reports\nwind.xml
5. Copy the contents of folder \FastReports\FastReport.Net\Demos\WCF to \Reports – it contains test reports with built-in connections to the database, which are essential when used with library FastReport.Service.dll
6. Open the configuration file FastReport.Service.dll.config in any text editor
7. Change the path to the reports in section

```
<add key="FastReport.ReportsPath" value="C:\WCF\FastReport\Reports" />
```


8. Change the connection string in section :

```
<add name="FastReportDemo" connectionString="XsdFile=;XmlFile=C:\WCF\FastReport\Data\nwind.xml"/>
```


9. Create batch file service.bat containing the line:

```
"C:\Program Files\Microsoft Visual Studio 10.0\Common7\IDE\WcfSvcHost.exe"  
/service:C:\WCF\FastReport\FastReport.Service.dll /config:C:\WCF\FastReport\FastReport.Service.dll.config
```

10. Run service.bat from Explorer with administrator rights ('Run as administrator'). You will see an icon for WCF Service Host in the system tray. Double-click on the icon:



11. Open a web browser and go to address <http://localhost:8732/FastReportService/>




This shows the Service working normally. You can change the port number of the service in the configuration file:


```
<add baseAddress="http://localhost:8732/FastReportService/" />
```

Let's connect to our service from the demo example \FastReport.Net\Demos\C#\WCFCClient


1. Open WCFSERVICECLIENT.csproj in Visual Studio
2. Right-click in Solution Explorer on "Service References:ReportService" and select "Configure Service Reference" in the popup



3. Review the service address, which should end with "/mex" (metadata exchange)



4. Compile and run an example.




Creating Web Service using FastReport.Service.dll

There is an easy way to implement a web service using the library FastReport.Service.dll (WCF Service Library), which is supplied with FastReport .Net.


Our example is based on creating a simple web application with web service functions, but you can modify your existing project based on .NET Framework 4.0 or later.

Run Visual Studio and create a new ASP.NET Web Application project under .NET Framework 4.0.



Add references to libraries FastReport.dll, FastReport.Bars.dll, FastReport.Service.dll

Create a new text file with name ReportService.svc in the site root.



Add these lines to the file:

```
<%@ ServiceHost Service="FastReport.Service.ReportService" %>  
<%@ Assembly Name="FastReport.Service" %>
```

Open web.config and add this code in section:

```

<appSettings>
  <!-- path to folder with reports -->
  <add key="FastReport.ReportsPath" value="C:\Program files\FastReports\FastReport.Net\Demos\WCF" />
  <!-- name of connection string for reports -->
  <add key="FastReport.ConnectionStringName" value="FastReportDemo" />
  <!-- Comma-separated list of available formats PDF,DOCX,XLSX,PPTX,RTF,ODS,ODT,MHT,CSV,DBF,XML,TXT,FPX.
  You can delete any or change order in this list. -->
  <add key="FastReport.Gear" value="PDF,DOCX,XLSX,PPTX,RTF,ODS,ODT,MHT,CSV,DBF,XML,TXT,FPX" />
</appSettings>
<connectionStrings>
  <add name="FastReportDemo" connectionString="XsdFile=;XmlFile=C:\Program
Files\FastReports\FastReport.Net\Demos\Reports\nwind.xml"/>
</connectionStrings>
<system.serviceModel>
  <services>
    <service behaviorConfiguration="FastReportServiceBehavior" name="FastReport.Service.ReportService">
      <endpoint address="" binding="wsHttpBinding" contract="FastReport.Service.IFastReportService">
        <identity>
          <dns value="localhost" />
        </identity>
      </endpoint>
      <endpoint address="mex" binding="mexHttpBinding" contract="IMetadataExchange" />
    </service>
  </services>
  <behaviors>
    <serviceBehaviors>
      <behavior name="FastReportServiceBehavior">
        <serviceMetadata httpGetEnabled="True" />
        <serviceDebug includeExceptionDetailInFaults="True" />
      </behavior>
    </serviceBehaviors>
  </behaviors>
  <bindings>
    <basicHttpBinding>
      <binding messageEncoding="Mtom"
closeTimeout="00:02:00" openTimeout="00:02:00"
receiveTimeout="00:10:00" sendTimeout="00:02:00"
maxReceivedMessageSize="67108864" maxBufferSize="65536"
transferMode="Streamed">
        <security mode="None">
          <transport clientCredentialType="None" />
        </security>
      </binding>
    </basicHttpBinding>
  </bindings>
</system.serviceModel>

```

The key "FastReport.ReportsPath" should contain a path to the folder with the reports. You can set it to the demo folder «\FastReport.Net\Demos\WCF», for example.


The key "FastReport.ConnectionStringName" should contain the connection string name. This line should be registered in section .

Let's run our site and check the availability of a Web service by accessing the file ReportService.svc.



When you deploy the project on the server, be sure to check that files FastReport.dll, FastReport.Bars.dll, FastReport.Service.dll are in the folder \bin.


Examples of client programs can be found in the folders \FastReport.Net\Demos\C#\WCFClient and \FastReport.Net\Demos\C#\WCFWebClient. Open each project in Visual Studio, right-click on ReportService and select Configure Service Reference in the popup.




Specify the address of an existing web service in the configuration window.

Creating the WCF service hosted in windows service


Open Visual Studio and create a project WindowsService.




Open the designer of Service1.cs




Change the name of the service to your own choice:




Right-click on window and select "Add Installer" in the popup:




Edit the properties of the component `serviceInstaller1` - set up a `DisplayName`.




In the component properties of `serviceProcessInstaller1` set the type of account for the service as `LocalSystem`.



Add references in the project to System.ServiceModel and FastReport.Service.dll :



Create an application configuration file:



Copy the following text into the new app.config file:

```
<?xml version="1.0"?>
<configuration>
  <appSettings>
    <!-- path to folder with reports -->
    <add key="FastReport.ReportsPath" value="C:\Program files\FastReports\FastReport.Net\Demos\WCF" />
    <!-- name of connection string for reports -->
    <add key="FastReport.ConnectionStringName" value="FastReportDemo" />
    <!-- Comma-separated list of available formats PDF,DOCX,XLSX,PPTX,RTF,ODS,ODT,MHT,CSV,DBF,XML,TXT,FPX.
    You can delete any or change order in this list. -->
    <add key="FastReport.Gear" value="PDF,DOCX,XLSX,PPTX,RTF,ODS,ODT,MHT,CSV,DBF,XML,TXT,FPX" />
  </appSettings>
  <connectionStrings>
    <add name="FastReportDemo" connectionString="XsdFile=;XmlFile=C:\Program
Files\FastReports\FastReport.Net\Demos\Reports\nwind.xml"/>
  </connectionStrings>
  <system.web>
    <compilation debug="true" />
    <membership defaultProvider="ClientAuthenticationMembershipProvider">
      <providers>
        <add name="ClientAuthenticationMembershipProvider"
type="System.Web.ClientServices.Providers.ClientFormsAuthenticationMembershipProvider,
System.Web.Extensions, Version=4.0.0.0, Culture=neutral, PublicKeyToken=31bf3856ad364e35" serviceUri=""
/>
      </providers>
    </membership>
    <roleManager defaultProvider="ClientRoleProvider" enabled="true">
      <providers>
        <add name="ClientRoleProvider" type="System.Web.ClientServices.Providers.ClientRoleProvider,
System.Web.Extensions, Version=4.0.0.0, Culture=neutral, PublicKeyToken=31bf3856ad364e35" serviceUri=""
cacheTimeout="86400" />
      </providers>
    </roleManager>
  </system.web>
  <!-- When deploying the service library project, the content of the config file must be added to the
host's
app.config file. System.Configuration does not support config files for libraries. -->
  <system.serviceModel>
    <services>
      <service behaviorConfiguration="FastReportServiceBehavior" name="FastReport.Service.ReportService">
        <endpoint address="" binding="wsHttpBinding" contract="FastReport.Service.IFastReportService">
          <identity>
            <dns value="localhost" />
          </identity>
        </endpoint>
        <endpoint address="mex" binding="mexHttpBinding" contract="IMetadataExchange" />
      </service>
    </services>
    <behaviors>
      <serviceBehaviors>
        <behavior name="FastReportServiceBehavior">
          <serviceMetadata httpGetEnabled="True" />
          <serviceDebug includeExceptionDetailInFaults="True" />
        </behavior>
      </serviceBehaviors>
    </behaviors>
    <bindings>
      <basicHttpBinding>
        <binding messageEncoding="Mtom"
closeTimeout="00:02:00" openTimeout="00:02:00"
receiveTimeout="00:10:00" sendTimeout="00:02:00"
/ >
      </basicHttpBinding>
    </bindings>
  </system.serviceModel>
</configuration>
```

```

maxReceivedMessageSize="67108864" maxBufferSize="65536"
transferMode="Streamed">
<security mode="None">
<transport clientCredentialType="None" />
</security>
</binding>
</basicHttpBinding>
</bindings>
</system.serviceModel>
<startup>
<supportedRuntime version="v4.0" sku=".NETFramework,Version=v4.0" />
</startup>
</configuration>

```

Go to the editor of Service1.cs and add the line:

```
using System.ServiceModel;
```

Modify the class of service so it looks like:

```

public partial class ReportService : ServiceBase
{
    ServiceHost reportHost;

    public ReportService()
    {
        InitializeComponent();
    }

    protected override void OnStart(string[] args)
    {
        if (reportHost != null)
            reportHost.Close();
        reportHost = new ServiceHost(typeof(FastReport.Service.ReportService));
        reportHost.Open();
    }

    protected override void OnStop()
    {
        reportHost.Close();
        reportHost = null;
    }
}

```

You can install the service using the command line utility InstallUtil.exe, which comes with .NET Framework, for instance:

```

C:\Windows\Microsoft.NET\Framework\v4.0.30319\InstallUtil.exe
"C:\MyProjects\WcfService1\WindowsService1\bin\Debug\WindowsService1.exe"

```

And you can start the service with the command:

```
net start ReportService
```

Open a web browser and check the address <http://localhost:8732/FastReportService/>, which was set in app.config in baseAddress. You can change the folder and port to your own choice.

Commands to stop and to uninstall the service:

```
net stop ReportService
```

```
C:\Windows\Microsoft.NET\Framework\v4.0.30319\InstallUtil.exe /u
```

```
"C:\MyProjects\WcfService1\WindowsService1\bin\Debug\WindowsService1.exe"
```

This example is located in folder "\Demos\C#\WCFWindowsService".

Working with Blazor

Presenting `FastReport.Web` package with components for embedding a web application into your [Blazor Server](#). Starting from version 2021.3, this library contains Razor components for the [Blazor Server](#) (server-side) application, which means that all operations will be performed on the server side, which will then pass the finished display to the client.

The minimum target framework at the moment is .Net Core 3.1 to ensure the highest possible compatibility with the latest LTS (long-term support) version. Also, most users have this version and it is compatible with the latest .NET 5 framework (within this package) and newer.

Preflight Preparation

To use Blazor components in `FastReport.Web`, you need to add a reference in your project file (csproj)

`PackageReference` specifying the id of this package and the `FastReport.Core` package (versions may differ):

```
<ItemGroup>
  <PackageReference Include="FastReport.Core" Version="2021.3.0-demo"/>
  <PackageReference Include="FastReport.Web" Version="2021.3.0-demo"/>
</ItemGroup>
```

Then, to simplify naming, we recommend adding the following namespaces to your project's imports (

`_Imports.razor` file):

```
@using FastReport.Web
@using FastReport.Web.Blazor.Components
@using FastReport.Web.Blazor.Components.Internal
```

In fact, just adding `FastReport.Web.Blazor.Components` may be enough, however, for some cases, you may need other namespaces as well.

Also, some components are likely to move within these namespaces during the beta version.

In the configurator of your web application, you need to call the `UseFastReport` method with an optional lambda expression for setting `FastReportOptions`.

Also, for some built-in common styles and SVG images of icons in Toolbar and Tab to work, you need to use the `UseStaticFiles` call (if you are not going to use Toolbar and Tabs, the `UseStaticFiles` call to use this package is optional):

```
public void Configure(IApplicationBuilder app, IWebHostEnvironment env)
{
  // ...
  app.UseStaticFiles();
  // ...
  app.UseFastReport();
  // ...
}
```

Description of built-in components

The following is a description of the components included in `FastReport.Web`. We do not recommend using components other than `WebReportContainer`, because they can be unstable outside of the standard component tree.

However, to fine-tune the rendering, you may need to use other components.

WebReportContainer

The main and most versatile Blazor component that performs `WebReport` rendering is `<WebReportContainer/>`. It is located in the namespace `FastReport.Web.Blazor.Components`.

The only parameter it takes is an object of the `WebReport` class. This means that to use this component, you must create an object of the `WebReport` class, assign it a `Report`, other necessary parameters, and pass this object to the `WebReportContainer` parameters.

Example

```
<WebReportContainer WebReport="@UserWebReport" />

@code {
    public WebReport UserWebReport { get; set; }

    protected override void OnParametersSet()
    {
        var report = Report.FromFile(
            Path.Combine(
                directory,
                "My report.frx"));

        // Registers the application dataset
        Report.RegisterData(DataSet, "NorthWind");

        UserWebReport = new WebReport();
        UserWebReport.Report = Report;
    }
}
```

This component can define a different Mode (Designer, Dialog, and normal Preview) and can prepare a report, embed default styles and individual styles, display Toolbar, Outline and Tabs, work with interactive reports, etc.

WebReportPreview

It is similar to the previous component but does not take into account the Designer Mode. That is, it always tries to prepare and render a report.

ReportContainer

It is similar to the previous component but does not include loading `WebReport` styles (common and individual for Toolbar/Tabs/Outline).

It is engaged in the preparation of the report and subsequent display together with the Toolbar and Tabs (if necessary).

When working with any interactivity (clicks on the report / working with dialog forms), it is this component that is updated.

ReportBody / ExportComponent

The `ReportBody` calls the Outline rendering (if necessary) and "nests" a component that is the rendering of the report itself (`ExportComponent`), which the `ReportContainer` passes to it. *Not recommended for use.*

BlazorExport

The "lowest" level of a component is not a component at all, but `BlazorExport` itself - a tool for exporting a prepared report to the `RenderTreeBuilder` build format. Located in `FastReport.Web.Blazor.Export` namespace.

To build this export, you must:

1. Prepare the report;
2. Make sure that this report does not use dialog forms (they are rendered using the `DialogPageComponent` and are not covered in this tutorial);
3. Create your own component and explicitly define the construction method in it (call the override of the `BuildRenderTree` method);
4. In this build method, create a `BlazorExport` instance, set the properties it needs, and call `Export` passing the following parameters: a `Report` and a builder instance that is an argument to this overridden method.

```
/// Main function
protected override void BuildRenderTree(RenderTreeBuilder builder)
{
    using (BlazorExport blazor = new BlazorExport())
    {
        blazor.StylePrefix = $"fr{WebReport.ID}";
        blazor.EmbedPictures = true;
        blazor.OnClick += ProcessClick;
        blazor.EnableMargins = WebReport.EnableMargins;
        blazor.SinglePage = true;
        blazor.CurPage = WebReport.CurrentPageIndex;

        blazor.Export(myReport, builder);
    }
}
```

Online Designer

At the moment, Online Designer can work in the `iframe` element using javascript and it is fully compatible with the Online Designer assembly for Core.

To use only the designer's capabilities, you can call the `<IFrameDesigner/>` component passing it the `WebReport` parameter with the configured Report property and the optional `DesignerLocale` and `DesignerPath` :

```
<IFrameDesigner WebReport="CurrentWebReport" />
```

However, we remind you that the `WebReportContainer` component understands which Mode it is currently working with and it is not at all necessary to call `IFrameDesigner` in this form.

Setting up common styles and SVG

Unlike `FastReport.Web` for Core, SVG images for Toolbar and Tabs, as well as some general display styles of Tabs, Outline, etc. have been moved to `staticWebAssets` for possible customization in your web application (changing colors, sizes, replacing images).

These resources are located in your local storage. At the time of development/assembly of your application, they are located at: `{UserName}/.nuget/packages/fastreport.web/{version}/staticwebassets`

At the time of publishing your web application (dotnet publish), these resources are copied to the directory:

`wwwroot/_content/FastReport.Web`

Demo project

You can find a project for demonstrating work with the `FastReport.Web` package on our [GitHub](#). An example of using the `WebReportContainer` is in the custom component under `Pages/Index.razor` and `Pages/Index.razor.cs`.

Extending FastReport functionality

Create your own connection types

Creating custom connection types

Data connections are used to add a data source to a report. This allows you to connect to data directly from the report, rather than using data provided by the application.

To create your own connection you need to do the following:

- create a connection class - a descendant of `FastReport.Data.DataConnectionBase` and implement some of its methods;
- create a connection editor - an heir of `FastReport.Data.ConnectionEditors.ConnectionEditorBase` and implement the user interface and methods `GetConnectionString` , `SetConnectionString` ;
- register the connection in FastReport.

These steps will be described below.

DataConnectionBase class

To create your own connection, use the FastReport.Data.DataConnectionBase class. This class has the following set of methods that you must override when creating your own connection:

```
public abstract class DataConnectionBase : DataComponentBase
{
    protected virtual string GetConnectionStringWithLoginInfo(string userName, string password)
    public abstract string QuoteIdentifier(string value, DbConnection connection);
    public virtual DbConnection GetConnection();
    public virtual DbDataAdapter GetAdapter(string selectCommand, DbConnection connection,
        CommandParameterCollection parameters);
    public virtual ConnectionEditorBase GetEditor();
    public virtual Type GetParameterType();
    public virtual string GetConnectionId();
    public virtual string[] GetTableNames();
    public virtual void TestConnection();
    public virtual void FillTableSchema(DataTable table, string selectCommand,
        CommandParameterCollection parameters);
    public virtual void FillTableData(DataTable table, string selectCommand,
        CommandParameterCollection parameters);
}
```

Not all methods need to be overridden - some of them have a default implementation, which will be sufficient for most cases. So, if your connection uses objects of type DbConnection and DbDataAdapter (and this is standard for the vast majority of connections), you need to implement the following methods:

```
public abstract string QuoteIdentifier(string value, DbConnection connection);
protected virtual string GetConnectionStringWithLoginInfo(string userName, string password)
public virtual DbConnection GetConnection();
public virtual DbDataAdapter GetAdapter(string selectCommand, DbConnection connection,
    CommandParameterCollection parameters);
public virtual ConnectionEditorBase GetEditor();
public virtual Type GetParameterType();
public virtual string GetConnectionId();
public virtual string[] GetTableNames();
```

If your connection does not work with such objects, but, for example, is a bridge between the application server and the report, you will need to implement the following methods:

```
public abstract string QuoteIdentifier(string value, DbConnection connection);
public virtual ConnectionEditorBase GetEditor();
public virtual Type GetParameterType();
public virtual string GetConnectionId();
public virtual string[] GetTableNames();
public virtual void TestConnection();
public virtual void FillTableSchema(DataTable table, string selectCommand,
    CommandParameterCollection parameters);
public virtual void FillTableData(DataTable table, string selectCommand,
    CommandParameterCollection parameters);
```

Below is a description of each method.

ConnectionString property

Each connection type has its own set of parameters, such as database path, SQL dialect, username and password. The ConnectionString property, which has a string type, is used to store the parameters.

This property is used as follows:

- in the GetConnection method when creating an object of type DbConnection;
- In the connection editor. In the latter case, individual parameters are selected from the connection string (e.g., the path to the database file). This uses a class of type `DbConnectionStringBuilder`, specific to each connection type. For example, for MS SQL it is `SqlConnectionStringBuilder`.

QuoteIdentifier method

An identifier (table or column name) is passed to this method. The method must return a quoted identifier. Quotation marks are specific to each database. For example, MS Access uses square brackets:

```
select * from [Table with long name]
```

The method in `MsAccessDataConnection` looks like this:

```
public override string QuoteIdentifier(string value, DbConnection connection)
{
    return "[" + value + "];"
}
```

You must override this method. Refer to the manual for this connection type to find out which characters are used to refer to tables with long names.

GetConnectionStringWithLoginInfo method

This method should take the existing connection string (from the `ConnectionString` property), include the username and password information, and return the modified string. This method is used if the connection settings specify "Ask for password when connecting".

For example, the implementation of this method for `MsSqlDataConnection` looks like this:

```
protected override string GetConnectionStringWithLoginInfo(string userName, string password)
{
    // get the existing connection string
    SqlConnectionStringBuilder builder = new SqlConnectionStringBuilder(ConnectionString);

    // include the username and password
    builder.IntegratedSecurity = false;
    builder.UserID = userName;
    builder.Password = password;

    // return the modified string
    return builder.ToString();
}
```

You have to override this method.

GetConnection method

The method returns a new object of type `DbConnection`, specific to this connection. This object is used to connect to the database when the table needs to be filled with data.

The connection parameters are taken from the `ConnectionString` property. For example, for `MsSqlConnection`, the method looks like this:

```
public override DbConnection GetConnection()
{
    return new SqlConnection(ConnectionString);
}
```

Most of the time you have to override this method. It is used in two other methods, `FillTableSchema` and `FillTableData`. If your connection type does not use `DbConnection` and `DbDataAdapter` objects to get information about the table and load data into it, you may not override this method. In that case, you must override the `FillTableSchema` and `FillTableData` methods.

GetAdapter method

The method returns a new object of type `DbDataAdapter`, specific to this connection. This object is used to fill the table with data.

The following parameters are passed to the method:

Parameter	Description
selectCommand	SQL query text.
connection	Object of type <code>DbConnection</code> , created in the <code>GetConnection</code> method.
Parameters	Query parameters, if defined.

Let's look at an example implementation of this method in `MsSqlDataConnection`:

```
public override DbDataAdapter GetAdapter(string selectCommand, DbConnection connection,
    CommandParameterCollection parameters)
{
    SqlDataAdapter adapter = new SqlDataAdapter(selectCommand, connection as SqlConnection);
    foreach (CommandParameter p in parameters)
    {
        SqlParameter parameter = adapter.SelectCommand.Parameters.Add(p.Name, (SqlDbType)p.DataType, p.Size);
        parameter.Value = p.Value;
    }
    return adapter;
}
```

The method creates an adapter specific to MS SQL, fills the query parameters and returns the adapter. The parameters should be described in more detail. The query text may contain parameters. In this case, a collection of parameters in the parameters variable is passed to the method - these are the parameters defined in the FastReport designer when the query was created. You must add the parameters to the `adapter.SelectCommand.Parameters` list. Each parameter in the parameters collection has the following properties:

Property	Description
Name	Parameter name.
DataType	The data type of the parameter. This is an int type property; you must cast it to the type used for the parameters in this connection.
Size	The size of the parameter data.
Value	The value of the parameter.

Most of the time you have to override this method. It is used in two other methods, `FillTableSchema` and `FillTableData`. If your connection type doesn't use the `DbConnection` and `DbDataAdapter` objects to get information about the table and load data into it, you may not override this method. In that case, you must override the `FillTableSchema` and `FillTableData` methods.

GetEditor method


This method returns an instance of the editor for the given connection type. The implementation of the editor will be discussed in "[Connection Editor](#)".

An example implementation of this method in `MsSqlDataConnection` :

```
public override ConnectionEditorBase GetEditor()
{
    return new MsSqlConnectionEditor();
}
```

GetParameterType method

The value returned by this method is used in the query parameter editor to select the data type of the parameter:



For example, for `MsSqlConnection` the parameter is of type `SqlDbType` :

```
public override Type GetParameterType()
{
    return typeof(SqlDbType);
}
```

You have to override this method.

GetConnectionId method

The value returned by this method is used in the "Connection Wizard" to display short information about the connection.

This value usually contains the name of the connection type and the name of the database. In `MsSqlDataConnection` the implementation of the method looks like this:

```
public override string GetConnectionId()
{
    SqlConnectionStringBuilder builder = new SqlConnectionStringBuilder(ConnectionString);
    string info = builder.InitialCatalog;
    if (String.IsNullOrEmpty(info))
        info = builder.AttachDBFilename;
    return "MS SQL: " + info;
}
```

Note that `SqlConnectionStringBuilder` is used to parse the connection string (`ConnectionString` property).

You have to override this method.

GetTableNames method

This method returns a list of tables and views in the database. As a rule, the `GetSchema` method of the `DbConnection` object is used for this, which is returned by the `GetConnection` method.

This method has a standard implementation. In case the standard implementation is incompatible with your connection type (i.e., it does not return a list of database entities), you will have to override this method. Consider the `MssqlDataConnection` implementation of this method as an example:

```
public override string[] GetTableNames()
{
    List<string> list = new List<string>();
    GetDBObjectNames("BASE TABLE", list);
    GetDBObjectNames("VIEW", list);
    return list.ToArray();
}

private void GetDBObjectNames(string name, List<string> list)
{
    DataTable schema = null;
    using (DbConnection connection = GetConnection())
    {
        connection.Open();
        schema = connection.GetSchema("Tables", newstring[] { null, null, null, name });
    }
    foreach (DataRow row in schema.Rows)
    {
        list.Add(row["TABLE_NAME"].ToString());
    }
}
```

TestConnection method

This method is called when you click the "Test" button in the connection settings.

The method has a default implementation that creates the connection and tries to open it:

```
public virtual void TestConnection()
{
    DbConnection conn = GetConnection();
    if (conn != null)
    {
        try
        {
            conn.Open();
        }
        finally
        {
            conn.Dispose();
        }
    }
}
```

If the test was successful, the method does nothing. Otherwise, an exception occurs when the connection is opened, which is handled in the "Connection Wizard" and gives a window with an error text.

As a rule, you don't need to override this method. You may need it if your connection does not use a `DbConnection` object to access the database (and therefore you do not return it in the `GetConnection` method).

FillTableSchema method

The method fills in the table schema (i.e. field names and types).

The following parameters are passed to the method:

Parameter	Description
table	The DataTable object whose schema you want to fill.
selectCommand	Query text in SQL.
parameters	Query parameters, if defined.

The method has a default implementation that uses objects returned by the `GetConnection` and `GetAdapter` methods:

```
public virtual void FillTableSchema(DataTable table, string selectCommand, CommandParameterCollection parameters)
{
    using (DbConnection conn = GetConnection())
    {
        OpenConnection(conn);

        // prepare select command
        selectCommand = PrepareSelectCommand(selectCommand, table.TableName, conn);

        // read the table schema
        using (DbDataAdapter adapter = GetAdapter(selectCommand, conn, parameters))
        {
            adapter.SelectCommand.CommandTimeout = CommandTimeout;
            adapter.FillSchema(table, SchemaType.Source);
        }
    }
}
```

In most cases, you do not need to override this method. You may need to do this if you don't use the `DbConnection` and `DbDataAdapter` objects to access the data (and therefore don't implement the `GetConnection` and `GetAdapter` methods).

FillTableData method

The method fills the table with data.

The following parameters are passed to the method:

Parameter	Description
table	The DataTable object to be filled.
selectCommand	Query text in SQL.
parameters	Query parameters, if defined.

The method has a default implementation that uses objects returned by the `GetConnection` and `GetAdapter` methods:

```
public virtual void FillTableData(DataTable table, string selectCommand, CommandParameterCollection parameters)
{
    using (DbConnection conn = GetConnection())
    {
        OpenConnection(conn);

        // prepare select command
        selectCommand = PrepareSelectCommand(selectCommand, table.TableName, conn);

        // read the table
        using (DbDataAdapter adapter = GetAdapter(selectCommand, conn, parameters))
        {
            adapter.SelectCommand.CommandTimeout = CommandTimeout;
            table.Clear();
            adapter.Fill(table);
        }
    }
}
```

In most cases, you do not need to override this method. You may need to do this if you don't use the `DbConnection` and `DbDataAdapter` objects to access the data (and therefore don't implement the `GetConnection` and `GetAdapter` methods).

Connection Editor

To edit the connection, use a control of type UserControl, which is displayed in the connection selection window (in the figure the control is highlighted with a red frame).


Each connection type has its own editor. All editors are inherited from the base class -

`FastReport.Data.ConnectionEditors.ConnectionEditorBase` :


```
public class ConnectionEditorBase : UserControl
{
    protected virtual string GetConnectionString();
    protected virtual void SetConnectionString(string value);
}
```

To create your own editor, do the following:


- Add a new control to the project (Add->User Control...) and select "Inherited User Control" in the "Add New Item" window:



- select the ConnectionEditorBase base class type:



A control that looks like this will be added to the project:



On the form of the editor, place the controls you need. Change the height of the editor to accommodate all the elements. The width of the editor is fixed and cannot be changed.

The methods of the base class allow you to fill the controls with values from the connection and, conversely, to pass values from the elements to the connection.

GetConnectionString method

This method is called when you close the editor window with the OK button. It should return a connection string that contains the values entered in the editor.

SetConnectionString method

This method is called the first time the editor is displayed. It must parse the connection string into its component parts and display their values in the editor. To parse a connection string, it is convenient to use a class of type `DbConnectionStringBuilder`, which is available in every connection type. For example, for MS SQL it is

`SqlConnectionStringBuilder`.

Registering a connection in FastReport

In order for your connection to be used in the FastReport designer, it must be registered. There are two ways to do this.

Method 1: Your connection is part of your project (i.e. it is not in a separate .dll plugin). Registration is done using the following code:

```
FastReport.Utils.RegisteredObjects.AddConnection(typeof(MyDataConnection));
```

This code must be executed once in the entire lifetime of the application, before you start the designer.

Method 2. Your connection is contained in a separate .dll plugin. In this case you can connect the plugin to FastReport, and it will be loaded every time you work with the designer. To do this, you need to declare a public class like `FastReport.Utils.AssemblyInializerBase` in the plugin and register your connection in its constructor:

```
public class AssemblyInitializer : FastReport.Utils.AssemblyInitializerBase
{
    public AssemblyInitializer()
    {
        FastReport.Utils.RegisteredObjects.AddConnection(typeof(MyDataConnection));
    }
}
```

When you load your plugin, FastReport will find classes like `AssemblyInitializerBase` and initialize them.

To attach a plugin to FastReport, bring up the designer and select the `Settings...` item in the View menu. In the window that opens, select the "Plugins" tab and add your .dll plugin.

This can also be done by adding the module name to the FastReport configuration file. This file is created in the user directory by default:

```
C:\Documents and Settings\User\Local Settings\Application Data\FastReport\FastReport.config
```

Add a plugin inside the `Plugins` tag:

```
<?xml version="1.0" encoding="utf-8"?>
<Config>
    ...
    <Plugins>
        <Plugin Name="c:\Program Files\MyProgram\MyPlugin.dll"/>
    </Plugins>
</Config>
```

Release Notes

[Version 2022.2](#)

[Version 2022.1](#)

[Version 2021.4](#)

FastReport .NET 2022.1

New features

Added new "Advanced Matrix" object:

	Anne Dodsworth	Michael Suyama	Steven Buchanan	Laura Callahan	Janet Leverling	Nancy Davolio	Robert King	Margaret Peacock	Andrew Fuller	Total
▼ Beverages (12)	\$19 642,56	\$11 538,20	\$30 998,53	\$23 297,85	\$45 297,41	\$46 725,36	\$66 404,83	\$52 324,21	\$40 463,25	\$336 692,18
1. Chal	3%	13%	3%	5%	4%	2%	1%	7%	4%	\$12 788,10
2. Chang	3%	16%	3%	5%	3%	7%	2%	9%	3%	\$16 374,96
3. Chartreuse verte	1%	39%	69%	29%	5%	4%	0%	7%	4%	\$42 732,54
4. Côte de Blaye	74%		20%		56%	50%	30%	56%	62%	\$144 728,74
5. Guarani Fantástica	1%	5%	1%	4%	1%	2%	1%	0%	1%	\$4 504,37
6. Ipoh Coffee				12%	14%	14%	3%	4%	9%	\$23 526,70
7. Lakkalikööri	5%	7%	2%	15%	7%	8%	1%	3%	3%	\$15 760,44
8. Laughing Lumberjack Lager				1%	0%		0%	1%	2%	\$2 396,80
9. Outback Lager	4%	5%		6%	3%	3%	2%	6%	3%	\$10 672,65
10. Rhönbräu Klosterbier	4%	8%	1%	6%	3%	3%	53%	2%	2%	\$49 212,49
11. Sasquatch Ale	1%	4%	0%	1%	2%		5%	1%	2%	\$6 350,40
12. Steeleye Stout	4%	4%	0%	17%	1%	6%	2%	3%	5%	\$13 644,00
► Condiments (12)	\$10 125,55	\$6 208,47	\$4 115,30	\$46 437,66	\$14 581,64	\$17 027,56	\$9 731,38	\$24 634,87	\$96 210,67	\$229 073,09
► Confections (13)	\$8 053,16	\$6 940,63	\$4 809,80	\$21 699,91	\$33 622,40	\$28 568,92	\$14 518,99	\$27 768,73	\$21 455,69	\$167 438,23
► Dairy Products (10)	\$21 101,13	\$17 039,04	\$21 769,63	\$56 269,47	\$32 320,84	\$36 022,98	\$27 621,86	\$33 549,80	\$23 812,55	\$269 507,29
► Grains/Cereals (7)	\$1 245,30	\$9 410,70	\$4 027,56	\$11 072,05	\$21 235,01	\$8 465,91	\$6 535,50	\$22 579,61	\$11 172,95	\$95 744,59
► Meat/Poultry (6)	\$9 676,66	\$9 003,69	\$11 488,20	\$16 395,28	\$20 502,62	\$15 038,47	\$101 176,72	\$70 867,14	\$129 873,60	\$383 022,36
► Produce (5)	\$314,81	\$11 560,71	\$18 734,02	\$12 016,52	\$11 960,85	\$32 206,25	\$10 753,38	\$17 186,56	\$24 376,48	\$139 109,58
► Seafood (12)	\$8 148,91	\$5 940,71	\$5 744,25	\$12 041,54	\$25 032,10	\$24 206,16	\$7 146,59	\$27 315,93	\$15 747,57	\$131 323,74
Total	\$77 308,07	\$77 642,13	\$101 687,28	\$199 230,28	\$204 552,84	\$208 261,60	\$243 889,24	\$276 226,85	\$363 112,76	\$1 751 911,04

Here is a list of its key features:

- row and column headers can contain groups and simple elements in any order. This allows you to build asymmetric reports;
- collapse buttons allow you to interactively manage the visibility of individual elements;
- sorting buttons allow you to interactively sort the matrix by the selected values, including the total values;
- Top N grouping allows you to display N values in the header, and group the remaining values into a separate element with the ability to expand;
- output of matrix headers in a stepped form;
- sorting headers by total values;
- a wide range of aggregate functions;
- support of custom aggregate functions;
- a wide range of special functions that allow you to get the values of totals, adjacent cells, as well as functions for calculating percentages;
- support for "Sparkline" and "Gauge" objects in data cells.

TopN group with ability to expand/collapse its elements

Expand/collapse matrix elements

Block or stepped layout

Top 5 customers		Total	Total
	Total	Others (84)	
▶ Beverages (12)	\$144 007,88	\$192 684,30	\$336 692,18
▶ Condiments (12)	\$123 407,20	\$105 665,89	\$229 073,09
▶ Confections (13)	\$54 823,13	\$112 615,09	\$167 438,23
▶ Dairy Products (10)	\$103 074,28	\$166 433,01	\$269 507,29
▶ Grains/Cereals (7)	\$31 368,01	\$64 376,58	\$95 744,59
▼ Meat/Poultry (6)	\$269 495,38	\$113 526,98	\$383 022,36
1. Alice Mutton	\$13 428,48	\$19 269,90	\$32 698,38
2. Mishi Kobe Niku	\$1 319,20	\$5 907,30	\$7 226,50
3. Pâté chinois	\$7 137,60	\$10 288,80	\$17 426,40
4. Perth Pasties	\$6 916,56	\$13 657,61	\$20 574,17
5. Thüringer Rostbratwurst	\$239 795,40	\$60 573,28	\$300 368,67
6. Tourtière	\$898,14	\$3 830,10	\$4 728,24
▶ Produce (5)	\$67 154,22	\$71 955,36	\$139 109,58
▶ Seafood (12)	\$31 732,55	\$99 591,19	\$131 323,74
Total	\$825 062,63	\$926 848,41	\$1 751 911,04

Sort elements by the total value

Matrix header can contain different types of elements

	2011	2012	2013	2014	2015	2012 to 2011 change	2012 to 2011 %
Andrew Fuller	3900	2100			1800	-1800	53,85%
Janet Leverling	6100	3200				-2900	52,46%
Nancy Davolio	3300	2700	3100		1700	-600	81,82%
Steven Buchanan			3999	8100			
Total	13300	8000	7099	8100	3500	-5300	60,15%

Special functions to get other cell's value

Learn more about this object in the [documentation](#).

Added GS1 DataBar barcodes: Limited, Omnidirectional, Stacked and Stacked Omnidirectional.



New properties: Config.CompilerSetting.ExceptionBehaviour and Config.CompilerSetting.Placeholder.


These properties allow you to customize the behavior when exceptions with invalid database field and table names occur.

Config.CompilerSetting.Placeholder is a string variable that is used to replace expressions with nonexistent names. By default, the value of this variable is an empty string.

Config.CompilerSetting.ExceptionBehaviour can have the following values: **ExceptionBehaviour.Default** - default behavior, as it was before. If there are errors with invalid names, an error message is displayed. Report preparation is interrupted. **ExceptionBehaviour.ReplaceExpressionWithExceptionMessage** - invalid expressions are replaced by the text of the exception message. Errors are not shown at that. Report preparation is not interrupted. **ExceptionBehaviour.ShowExceptionMessage** - A message appears with the exception text, after pressing **OK**, report preparation continues. Incorrect expressions are replaced with the value of **Placeholder** variable. **ExceptionBehaviour.ReplaceExpressionWithPlaceholder** - invalid expressions are simply replaced with **Placeholder**. No error messages. Report preparation is not interrupted.

Example with variable values: **ExceptionBehaviour =**

ExceptionBehaviour.ReplaceExpressionWithPlaceholder Placeholder = "NO DATA!"



Here you can see that the table has a field named **FistName**, but it's not specified correctly in the expression.

EMPLOYEES

NO DATA! Fuller

Hire date: 14.08.2009
Birth date: 19 февраля 1972 г.
City: Tacoma
Address: 908 W. Capital Way
Phone: (206) 555-9482

Notes: Andrew received his BTS commercial in 1994 and a Ph.D. in international marketing from the University of Dallas in 2001. He is fluent in French and Italian and reads German. He joined the company as a sales representative, was promoted to sales manager in January 2009 and to vice president of sales in March 2010. Andrew is a member of the Sales Management Roundtable, the Seattle Chamber of Commerce, and the Pacific Rim Importers Association.



NO DATA! Dodsworth

Hire date: 15.11.2011
Birth date: 27 января 1986 г.
City: London
Address: 7 Houndstooth Rd.
Phone: (71) 555-4444

Notes: Anne has a BA degree in English from St. Lawrence College. She is fluent in French and German.



And this is the result of preparing such a report. Previously it would have been impossible to prepare it due to errors.

Improved translation quality of RTF into report objects.

Conversion of RTF into report objects is optimized. RTF translation in table cells is added. Lots of bugs fixed.

Exports improvements

Implemented export of watermark to Word and RTF.

Added SVG image scaling in export matrix.

This improves the quality of exported images when exporting to Word and Excel. However, this increases the size of the output file. To use this feature, you must enable the "Print optimized" option when exporting.

Export groups to single sheets in Excel 2007 has been implemented.

Excel 2007 has added the ability to export a property that determines the size and location of the image when exporting.

Now you can define how the image will behave in a cell when its position and size are changed. In doing so, the image can:

- move and resize together with the cell
- move together with the cell, but not change its size
- don't move or resize

Implemented the ability to hide or show grid lines when exporting to Excel 97.

Added "Don't rotate landscape pages when printing" option in HTML export.

Previously, we were forcibly rotating landscape-oriented pages when printing. The reason was that browsers

cannot correctly print reports with pages both in portrait and landscape orientation. When you print such documents, pages with landscape orientation are cut off by the width of pages with portrait orientation. Now, you can adjust whether to rotate pages in landscape orientation or not. In addition, a bug where landscape-oriented pages were always rotated, even when there are no portrait-oriented pages, has been fixed.


.NET 6 support

Added .NET 6 support for FastReport.Core and FastReport.CoreWin.

Improvements to WebReport for Core and Blazor Server

Export settings


Added the ability to configure the export of a report in the required format from WebReport. When the **webReport.Toolbar.Exports.EnableSettings** property is activated, the settings icon will appear next to the required export button. Clicking on this button will display a window with a list of possible settings (exported pages, properties, etc.).



The export settings window can be customized using the **webReport.Toolbar.Exports.Color** and **webReport.Toolbar.Exports.FontSettings** properties.

Separating different report pages into bookmarks

Added the ability to open different ReportPage pages in different WebReport tabs. To activate this feature, you need to enable the **webReport.SplitReportPagesInTabs** option.



Static Styles in WebReport

To be able to override the standard styles of the toolbar, outline and other elements for your own customization, static class names have been added. These include: `fr-toolbar`, `fr-toolbar-item`, `fr-toolbar-narrow`, `fr-toolbar-dropdown-content`, `fr-toolbar-zoom-selected`, `fr-toolbar-pointer`, `fr-toolbar-notbutton`, `fr-toolbar-slash`.

Complete list of changes

[Engine]

- added a new AdvMatrixObject
- added GS1 DataBar barcodes: Limited, Omnidirectional, Stacked and Stacked Omnidirectional
- added new properties: Config.CompilerSetting.ExceptionBehaviour and Config.CompilerSetting.Placeholder. These properties give the ability to customize the behavior when exceptions are thrown with incorrect names of database tables and fields.
- added translation of RichObject inside TableCell
- reworked translation of RichObject into report objects
- fixed ShiftMode of translated RTF object
- fixed a bug with two parameters with the same name in report leading to System.ArgumentException
- fixed a bug with subreport containing multicolumn Databand
- fixed a bug with wrong band height calculation
- fixed a bug with displaying of hyperlinks when converting RTF to report objects
- fixed translation of RichObject if it set from a report script
- fixed a bug with private fonts added to Config.PrivateFontCollection

[.Net Core]

- added support for .NET 6
- fixed incorrect search for Bold-Italic fonts

[Designer]

- added verification of entered data in editing window of the QR code of SberBank
- fixed a bug with line break in text object editor
- fixed a bug when converting rdl reports containing matrices inside table cells

- fixed a bug with guide lines in the designer
- fixed a bug with Report tree window
- fixed a bug leading to System.NullReferenceException and crash of the designer during its launch when the Auto Guides option is enabled

[Preview]

- fixed a bug with shifting the position of objects when switching the view of bands while editing a prepared page

[Exports]

- implemented export of watermark to Word
- implemented export of watermark to RTF
- added "Don't rotate landscape pages when printing" option in export to HTML
- added the ability to change the name of the attached file when sending by Email
- add zooming of SVG images in export matrix
- added the ability to export a property that determines the size and position of the image when exporting to Excel 2007
- implemented ability to hide or show gridlines when exporting to Excel 97
- implemented export of groups on separate sheets to Excel
- implemented export of transparency level watermark images to Word
- implemented export image size of watermark to RTF
- fixed a bug leading to System.NullReferenceException when exporting to text, tables with rows count less than one
- fixed incorrect left padding of tables in export to Word
- fixed a bug with Wingdings font in HTML tags when exporting to HTML
- fixed a bug with export Wingdings and Webdings fonts to HTML
- fixed a bug with width of frame in export to PowerPoint
- fixed a bug with exporting objects with transparent fill to RTF
- fixed a bug with exporting objects with transparent fill to Word
- fixed a bug leading to System.OutOfMemoryException when exporting to PDF
- fixed incorrect line break display when exporting to HTML
- fix out of memory when export to PDF
- fixed bugs in export to PDF in non-Windows systems
- fixed a bug with exporting tables with more than 63 columns to Word 2007
- fixed a bug leading to a memory leak and System.OutOfMemoryException in PDF-export when the "Text in curves" option is enabled
- fixed a bug with line break in HTML-export

[WebReport]

- fixed a bug with new line character when using Wingdings font

[WebReport Core / Blazor Server]

- added the ability to configure the properties of exporting a report from WebReport. When the webReport.Toolbar.Exports.EnableSettings property is activated, the settings icon will appear next to the required export button
- added property webReport.SplitReportPagesInTabs, which allows you to split different ReportPage-s in different tabs of WebReport
- added static class names for the ability to override the standard styles of toolbar, outline and other elements
- fixed updating WebReport when entering a value from the keyboard in the DateTimePicker field
- fixed the width of tabs with non-standard sizes of the report page

[Demos]

- added demo of using WebReport Core for .NET 5
- added demo of using WebReport Core for Angular
- added demo of using WebReport Blazor for Blazor Server


FastReport .NET 2021.4

Editions changes

The WinForms and Win+WebForms editions are gone. Instead, a new Standard edition has been added that includes Windows Forms components, ASP.NET components, and .NET Core / .NET 5 / Blazor support.

New features

- Added new Visual Studio-styled icons. You may switch between icon packs in the "View/Options/User Interface" window (or, "File/Options/User Interface" if you use ribbon UI):



The new icons are well suited for hiDPI screens.

- Added ability to reset the FastReport configuration stored in the `FastReport.Config` file in the user's profile. It can be done in the "View/Options/User Interface" window, the "Reset config" button. Restart of the designer is required in order to apply changes.
- Added ability for the Text object to display DB field names in a simplified form when designing a report. You can activate this option in the "View/Options/Objects appearance" window. This option is off by default. When you turn it on the Text object with a single DB field will display the field name part only, with no datasource name:

CUSTOMERS ORDERS			
[Orders.Customers.CompanyName]			
OrderID	[Orders.OrderID]	OrderDate	[Orders.OrderDate]
ShippedDate	[Orders.ShippedDate]		
Product name		Unit Price	Quantity
[Order Details.Products.ProductName]		[Order Details.UnitPrice]	[Order Details.Quantity]
Total this order: [SumOfOrder]			
Generated by FastReport .NET			[PageN]

It makes the report look cleaner especially when it contains a lot of small objects. You still can see a full text of object in the status bar.

- Added ability to set up each cell in the Matrix object's corner area. To do this use the cell's context menu and its commands "Split cell", "Merge cells":


Name	[Year]		Total
	[Month]	Total	
[Name]	[Revenue]		
Total			

Generated by FastReport .NET

- Added ability to connect to Elasticsearch. Connection available in data wizard and from code.
- Added barcode Japanese Post 4 - State Code.



- Added the collapse all/expand all buttons and, a search field for the report tree and data tree in the designer. When clicking on **+** tree will expand. On **-** tree will collapse.



These changes should simplify working with reports containing many objects and/or data sources.

- The RichText to report objects converter has been significantly improved and optimized.
- The number of available exports in WebReport Core/Blazor Server has increased significantly.
- Added FastReport Business Graphics integration objects (\Extras\Objects\FastReportBGOjects).

Universal plugins FastReport.Data

Packages with FastReport.Data plugins have been updated. Now they include plugins for different FastReport editions (.NET, Core, CoreWin, OpenSource) and automatically connect the necessary library, depending on the product you use. The FastReport edition 2021.3.0 or higher is required for correct work.

The FastReport.Core.Data, FastReport.CoreWin.Data, and FastReport.OpenSource.Data plugins are declared obsolete and are no longer supported.

Improvements in publishing user applications using FastReport

For user applications on .NET Core 3.0+ and .NET 5+ using FastReport.Core, FastReport.CoreWin, FastReport.OpenSource has been added [Single File Applications \(SFA\)](#) support.

Also, added support for publishing [application with trimmed unused libraries](#) - MSBuild property - PublishTrimmed*.

Warning! In some cases you may need to explicitly specify the list of builds that .NET should not trim. This may be useful if your report script uses these libraries, but your application's code does not make use of them.

This is done using the `TrimmerRootAssembly` property. In this case, for example, it's explicitly stated that the `System.Security` library doesn't need to be trimmed:

```
<ItemGroup>
  <TrimmerRootAssembly Include="System.Security" />
</ItemGroup>
```

Localizations

In the logic of the localization change small changes were made.

1. Added package **FastReport.Localization**. This package contains localization files for FastReport.NET, FastReport.Core, FastReport.CoreWin, FastReport.Mono, FastReport.OpenSource products and creates the Localization directory in the output directory of the user project when adding this package.
2. Added new API for changing the localization using the `CultureInfo` type - `FastReport.Utils.Res.LoadLocale(CultureInfo culture)`.

When this method is called, FastReport searches for the appropriate localization for the selected culture. Loaded locales are cached. For this method to work correctly, you must install the FastReport.Localization package from step 1 in your project or set the path to the folder with the localization files in the `FastReport.Utils.Res.LocalesFolder` property.

Changes and improvements in the WebReport Core/Blazor toolbar

- Toolbar settings were moved from `WebReport` class to `WebReport.Toolbar` property of `ToolbarSettings` class.
- Added toolbar settings: Position, color of dropdown menu, font, transparency of icons, changing icon color, changing content position. These properties are available in the `webReport.Toolbar`.
- During report loading, the toolbar is no longer displayed.
- Added the `ShowOnDialogPage` property to the `Toolbar` object (true by default), which will allow to turn off the toolbar rendering if a dialog window is currently open
- Added more exports to the toolbar dropdown menu. These properties are available in `webReport.Toolbar.Exports.ExportTypes`. List of added exports: HTML, Hpgl, Dxf, Json, LaTeX, Ppml, PS, Xaml, Zpl, Excel97, Svg.

```
ToolbarSettings toolbar = new ToolbarSettings()
{
    Color = Color.LightBlue,
    DropDownMenuColor = Color.LightBlue,
    ShowOnDialogPage = false,
    DropDownMenuTextColor = Color.Black,
    IconColor = IconColors.Black,
    Position = Positions.Right,
    FontSettings = new Font("Arial", 14, FontStyle.Bold),
    Exports = new ExportMenuSettings()
    {
        ExportTypes = Exports.Pdf | Exports.Excel97 | Exports.Rtf
    }
    // or
    //Exports = ExportMenuSettings.All
};
webReport.Toolbar = toolbar;
```

[Learn how to build this report on the Fast Reports Academy channel](#)


Demonstrates a simple list report. To create it:

- go to "Data" menu and select "Choose Report Data..." item to select a datasource;
- go to "Report|Configure Bands..." menu to create the band structure;
- return to the report page, doubleclick the data band to show its editor;
- choose the datasource;
- drag data from the Data Dictionary window to the band.

Export to PDF
Export to Rich Text
Export to Excel 97

EMPLOYEES

Andrew Fuller

<p>Hire date: 14.08.2009</p> <p>Birth date: 19 февраля 1972 г.</p> <p>City: Tacoma</p> <p>Address: 908 W. Capital Way</p> <p>Phone: (206) 555-9482</p> <p>Notes: Andrew received his BTS commercial in 1994 and a Ph.D. in international marketing from the University of Dallas in 2001. He is fluent in French and Italian and reads German. He joined the company as a sales representative, was promoted to sales manager in January 2009 and to vice president of sales in March 2010. Andrew is a member of the Sales Management Roundtable, the Seattle Chamber of Commerce,</p>	
---	---

WebReport Core/Blazor Server improvements

Added support for [Blazor Server components](#) for FastReport.Core3.Web package (CoreWin).

Improved support for dialog report components:

- DateTimePicker has been improved. In DateTimePicker.Format.Time mode it displays only time, in DateTimePicker.Format.Short mode - only date, DateTimePicker.Format.Long - both date and time

DateTimePicker1 Short:

02.09.2021


DateTimePicker2 Long:


11.03.2013

02:00:10


DateTimePicker3 Time:

14:24:33


- Added support of MaxLength property for TextBox
- Added support for the Enabled property
- Added support for background-color



Fixes

- Fixed bug with `Dock` and `Anchor` properties of the objects that are inside the Table/Matrix cell.
- Fixed stack overflow bug when you add `Subreport` object to the page footer band.
- Fixed bug with SVG export if the system's DPI setting is greater than 96DPI.

Complete list of changes

[Engine]

- added connection to ElasticSearch
- added a new barcode - Japanese PostNet
- added the `Res.LoadLocale (CultureInfo)` method, which changes the selected locale by the `CultureInfo` argument. Loaded locales are cached. For correct operation, the added `FastReport.Localization` package is required
- optimized and unified converter `RichText` to report objects
- fixed a bug with incorrect tab width when `TextObject.TextRenderType = TextRenderType.HtmlTextRenderer`
- fixed a bug with `SubreportObject` on a page footer band which caused `StackOverflow` exception
- fixed a bug with `Dock` and `Anchor` properties of objects inside table/matrix cells
- fixed a bug leading to `System.ArgumentException` when drawing `PictureObject` located outside the band
- fixed a bug with incorrect work of right anchor (`Anchor = AnchorStyles.Right`) when page has unlimited width
- fixed a bug with replacing a custom font with a default font when preparing a report
- fixed a bug with vertical alignment when converting RTF (by default, now `Top` instead of `Center`)
- fixed a bug with converting RTF tables to report objects

[Designer]

- added simplified display of DB field names in the designer
- added collapse all/expand all button and search field for Report tree and Data tree
- new icons added. Use the designer's "View|Options|User interface" dialog to switch between icon packs.
- fixed a bug leading to the crash of the report designer with an incorrect table in the data source.

[Preview]

- fixed a bug with saving prepared reports containing converted `RichObject`

[Exports]

- added option when export to Word 2007 "Do not add section breaks on page breaks". By default, both page breaks and section breaks are added.
- fixed page-break in Html export (PageBreaks property)
- fixed SVG export with "Multiply export" parameter
- fixed SVG export bug on hidpi monitor
- fixed the names of files saved in the zip archive
- fixed tab symbols width when export RichObject
- fixed XPS export bug where documents exported on Linux would not open on Windows
- fixed bugs with incorrect work of Anchor and Dock properties when exporting pages with unlimited width
- fixed a bug in Excel 2007 export of text objects with enabled HtmlParagraph render type. Disable WYSIWYG export option to export text instead of images.

[WebReport]

- added background-color support for dialogs in WebReport
- added support for the Enabled property for dialogs in WebReport
- added support for the MaxLength property for the TextBox dialog component in WebReport
- optimized loading of localization for Toolbar
- fixed incorrect page background-color for HTML/Blazor export on Safari browsers
- fixed a bug with hanging of online designer save call-back in WebReport with sessions
- fixed bugs with incorrect work Anchor and Dock properties on pages with unlimited width

[Online Designer]

- fixed save/preview from OnlineDesigner with page in Landscape orientation

[.Net Core]

- added support for Single File Application
- updated dependencies for FastReport.Compat and FastReport.DataVisualization. FastReport.Compat now correctly detects the possibility of using the WinForms API. FastReport.DataVisualization now has no dependency on System.Data.SqlClient and System.Drawing.Common
- fixed a bug where the report did not work with data from the custom library, although it was registered with ReferencedAssemblies in CoreWin
- fixed application crash when loading a report with unknown Font in multiple threads on Linux
- fixed a bug "Could not load type 'System.Drawing.Design.UITypeEditor'"
- fixed loading of table names in XmlDataConnection
- fixed a bug due to which the report and resources were not loaded when publishing/debugging using IIS/IIS Express. For correct work, you need to call the `UseFastReport()` method before 'UseMvc/UseEndpoints'

[WebReport Core/Blazor Server]

- added support for Blazor components for FastReport.Core3.Web package
- fixed incorrect output of multiline text in Blazor (Interactive Forms & TextBox)
- added xml comments (DocumentationFile) to Web libraries
- added a property to disable showing of the toolbar on the dialog page of the report: `webReport.Toolbar.ShowOnDialogPage`
- added more exports to the toolbar dropdown menu. These properties are available in `webReport.Toolbar.Exports`
- added the ability to customize the toolbar: Position, color of the drop-down menu, font, transparency of icons, change the color of icons, change the position of content. These properties are available in `webReport.Toolbar`
- dialog DateTimePicker for WebReport has been improved. In `DateTimePicker.Format.Time` mode, it displays

only time, in DateTimePicker.Format.Short mode - only date, DateTimePicker.Format.Long - both date and time.

- fixed missing line breaks for the Label dialog component in WebReport

[Extras]

- added package 'FastReport.Localization', which includes FastReport localization files in your project for working with different languages
- added FastReport Business Graphics integration objects (\Extras\Objects\FastReportBGObjects)

[Demos]

- implemented transition to list of reports, when clicking on the arrow on folder in new demo
- changed Target Framework for new demo to 4.7.2
- changed color of inactive buttons in the thumbnail view mode of new demo
- changed background color of the zoom slider in new demo
- changed background color when displaying dialog forms in the new demo
- changed background color of interactive reports tabs in new demo
- changed the location of the folder with report thumbnails for the demo application. Now this folder is located not in Program Files but in AppData\Local
- fixed problems with displaying interface elements of the new demo application
- fixed a bug that caused saving a prepared report when clicking on the drop-down items in the save menu of the new demo application
- fixed a bug with alignment of reports in preview window of the new demo
- fixed a bug with double launching dialog forma when selecting a report in new demo
- fixed a bug with stretching thumbnails in the new demo
- fixed a bug leading to a lag when moving the window of new demo
- fixed a bug in the new demo with simultaneous displaying of thumbnails in folder and report bars

[Plugins]

- packages with plugins-connectors FastReport.Data have been updated. Now they include plugins for different FastReport editions (.NET, Core, CoreWin, OpenSource) and automatically include the necessary library, depending on the product used
- postgres npgsql version downgrade from 4.0.3 to 3.2.7

Contacts and technical support

You can always ask questions about using the product by [email](#), or by using [the form on the website](#).

We also welcome your suggestions on how to improve our product.